



Franklin Fibre-Lamitex Corporation
903 East 13th Street, Wilmington, DE 19802 USA
Phone: 302.652.3621 Toll Free: 800.233.9739
Fax : 302.571.9754
Email: info@franklinfibre.com
Web: www.franklinfibre.com

SAFETY DATA SHEET

Arclex M

Section 1:
Chemical Product
and Company
Identification

Product Name: Arclex M
Manufacturer: Franklin Fibre-Lamitex Corporation
903 East 13th Street
Wilmington, DE 19802
Emergency Phone: 302.652.3621

Section 2:
Hazard(s)
Identification

GHS Classification
Respiratory Sensitization, Category 1B

GHS hazard phrase

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Placard

Health hazard

Key word

Danger

Hazard Phrases

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

GHS Precaution Phrases

Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/
mist/vapors/spray. In case of inadequate ventilation, wear respiratory protection.

GHS Response Phrases

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable
for breathing.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a
position comfortable for breathing. If experiencing respiratory symptoms call a
POISON CENTER or doctor/physician.

GHS Storage and Disposal Phrases

Dispose of contents/container to unregulated waste.

Arclex M

Section 2:
Hazard(s)
Identification
(continued)

Target Organs

Cardiovascular system, Eyes, Gastrointestinal System, Heart, Lungs, Respiratory system, Muscles, Skin.

Potential Health Effects (Acute and Chronic)

Mica is not listed as a carcinogen by OSHA, NTP, or IARC. However, IARC concludes that there is limited evidence of carcinogenicity of crystalline silica to humans. Excessive inhalation of dusts may cause lung injury with symptoms including shortness of breath and reduced pulmonary function. Persons with pre-existing respiratory disorders may be at an increased risk from exposure.

Inhalation

Inhalation of this material, particularly dust, may cause upper respiratory and mucous membrane irritation.

Even though this material which is made from natural mica (Phlogopite) contains fluorine ions, these ions are unlikely to leach out of formulation due to the high heat used in manufacturing process.

Skin Contact

Even though Phlogopite particles are large and insoluble in water, it may cause drying of the skin.

Eye Contact

Contact may cause mechanical irritation with redness, tearing and pain.

Ingestion

If ingestion occurs, muscle spasm, slow pulse, extra systoles, hyperkalemia may occur.

Medical Conditions Generally Aggravated By Exposure

None.

Section 3:
Composition/
Information on
Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Phlogopite	12251-00-2	58%
2. Frits, chemicals	65997-18-4	38-40%
3. Cryolite	15096-52-3	2-4%

Section 4:
First-Aid Measures

Emergency and First Aid Procedures

If exposure occurs, move to fresh air. Call a physician.

In Case of Inhalation

If an adverse reaction is observed or irritation develops, remove the person from source of exposure to fresh air. If symptoms persist get medical attention.

In Case of Skin Contact

Wash the exposed skin with soap and water. If irritation or rash develops get medical attention.

In Case of Eye Contact

If dust enters eyes, flush immediately with clean water for 15 minutes and call a physician.

Arclex M

Section 4:
First-Aid Measures
(continued)

In Case of Ingestion

Clear material from mouth. If large amounts of material are swallowed seek medical attention. No harmful effects are expected from a small ingestion.

Signs and Symptoms Of Exposure

Signs and symptoms of exposure include upper respiratory irritation, gastrointestinal irritation, muscle spasm, extra systoles, bradycardia (slow pulse), hypokalemia (low potassium), and skin and eye irritation, burns.

Section 5:
Fire-Fighting
Measures

Flash Point: NA **Auto Ignition Point:** NA **UEL:** NA

Explosion Limits: NA **LEL:** NA

Fire Fighting Instructions

Wear positive pressure, self-contained breathing apparatus for firefighting. Use structural firefighting clothing.

Flammable Properties and Hazards Suitable Extinguishing Media

This material is not flammable or combustible but rather becomes molten. Use any media appropriate for the surrounding fire, water fog, carbon dioxide, foam or dry chemical.

Unsuitable Extinguishing Media- NA

Section 6:
Accidental Release
Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Wear appropriate protective clothing and equipment. Sweep or vacuum up, avoiding the creation of airborne dust, and collect in a suitable container for disposal. Dust collectors may be used as well.

Protective Precautions, Protective Equipment and Emergency Procedures

Use a NIOSH approved dust/mist respirator if dust is created.

Section 7:
Handling and
Storage

Precautions To Be Taken in Handling

Avoid generating and breathing dust. Avoid eye contact. Use with adequate ventilation. If clothing becomes contaminated, remove and launder before reuse. Wash thoroughly before eating and drinking.

Food, beverages and smoking materials should not be allowed in the work area.

Precautions To Be Taken in Storing

Store in a dry area away from food and feed products. Avoid dust formation.

Other Precautions

Mica is not listed as a carcinogen by OSHA, NTP, or IARC. However, IARC concludes that there is limited evidence of carcinogenicity of crystalline silica to humans. Excessive inhalation of dusts may cause lung injury with symptoms including shortness of breath and reduced pulmonary function.

Arclex M

Section 8: Exposure Controls/ Personal Protection	Hazardous Components (Chemical Name)	CAS Number	OSHA PEL	ACGIH TLV
	1. Phlogopite	12251-00-2	3 mg/m ³	3 mg/m ³
	2. Frits, chemicals	65997-18-4	15 mg/m ³	10 mg/m ³
	3. Cryolite	15096-52-3	2.5 mg/m ³ (as F)	2.5 mg/m ³ (as F)

Respiratory Equipment (specify type)

For operations where the exposure limit may be exceeded and dust is generated, a NIOSH approved high efficiency particulate respirator is recommended. Equipment selection depends on contaminates type and concentration. Select in accordance with 29CFR1910.134 and good industrial hygiene practice.

Eye Protection

Normal eye protection should be employed for plant operations. For dusty operations goggles may be required.

Protective Gloves

Other Protective Clothing

Engineering Controls (Ventilation etc.)

Keep area well ventilated.

Work/Hygienic/Maintenance Practices

Wash hands and face thoroughly after exposure.

Section 9: Physical and Chemical Properties	Physical State:	[] Gas [] Liquid [X] Solid
	Appearance and Odor:	Light brown, odorless, solid or rod
	Melting Point: 750°C	Evaporation Rate: NA
	Boiling Point: NA	Solubility in Water: None
	Specific Gravity (water = 1): 2.5	Percent Volatile: NA
	Density: NA	Saturated Vapor Concentration: NA
	Vapor Pressure (vs. Air or mm Hg): NA	Viscosity: NA
	Vapor Density (vs. Air = 1): NA	pH: NA

Section 10: Stability And Reactivity	Stability:	Unstable []	Stable [X]
	Conditions to Avoid – Instability:	NA	
	Incompatibility - Materials To Avoid:	NA	
	Hazardous Decomposition Or Byproducts:	NA	
	Possibility of Hazardous Reactions:	Will occur	Will not occur [X]
	Conditions to Avoid - Hazardous Reactions:	NA	

Section 11: Toxicological Information	Toxicological Information					
	This product is composed of natural and synthetic clay minerals which are not acutely toxic by ingestion, inhalation or dermal contact.					
	Hazardous Components (Chemical Name)	CAS Number	NTP	IARC	ACGIH	OSHA
	1. Phlogopite	12251-00-2				
	2. Frits, chemicals	65997-18-4				
	3. Cryolite	15096-52-3				
	Carcinogenicity:					
	NTP? No		IARC Monographs? No			OSHA Regulated? No

Arclex M

Section 12: Ecological Information	Results of PBT and vPvB assessment (<i>Persistent and Bioaccumulative/very Persistent and very Bioaccumulative Chemical</i>) NA Persistence and Degradability NA Bioaccumulative Potential NA Mobility in Soil NA
Section 13: Waste Disposal Method	Waste Disposal Method Disposal of material should be done in compliance with all local, state, provincial and federal laws and regulations. Dispose of contents/containers to unregulated waste.
Section 14: Transport Information	Note: Not classified as dangerous in the meaning of transport regulations. DOT: Not regulated (US Department of Transportation) IMDG: Not regulated (International Maritime Dangerous Goods) IATA: Not regulated (International Air Transport Association) ICAO: Not regulated (International Civil Aviation Organization)
Section 15: Regulatory Information	SARA 302 Components: No subject to the reporting requirements of SARA Title III, Section 302. SARA 313 Components: This material does not contain any chemical component with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. SARA 311/312 Hazards: No SARA hazards. US EPA TSCA Inventory: The following component is not listed on the Toxic Substances Control Act Inventory. Phlogopite CAS N° 12003-28- The following components are listed on the Toxic Substances Control Act Inventory. Frits, chemicals CAS N° 65997-18-4 Cryolite N° 15096-52-3
Section 16: Other Information	Revision date 11/1/2015

FRANKLIN cannot anticipate or control the many different conditions under which this information and our products may be used. THE PRODUCTS DISCUSSED ARE SOLD WITHOUT WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, EITHER EXPRESSED OR IMPLIED, EXCEPT AS PROVIDED IN OUR STANDARD TERMS AND CONDITIONS OF SALE. This information supersedes all previously published data.